# Lighting

**PHILIPS** 

# G A G

# MASTER TL-D Super 80

# MASTER TL-D Super 80 58W/840 1SL/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

#### Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General information		Luminous Flux (Rated) (Nom)	5240 lm		
Cap-Base	G13 [ Medium Bi-Pin Fluorescent]	Color Designation	Cool White (CW)		
Life To 10% Failures (Nom)	12000 h	Chromaticity Coordinate X (Nom)	0.38		
Life to 50% Failures (Nom)	15000 h	Chromaticity Coordinate Y (Nom)	0.38		
Life to 50% Failures Preheat (Nom)	20000 h	Correlated Color Temperature (Nom)	4000 K		
LSF 2000 h Rated	99 %	Luminous Efficacy (rated) (Nom)	90 lm/W		
LSF 4000 h Rated	99 %	Color Rendering Index (Nom)	80		
LSF 6000 h Rated	99 %	LLMF 2000 h Rated	96 %		
LSF 8000 h Rated	99 %	LLMF 4000 h Rated	95 %		
LSF 12000 h Rated	89 %	LLMF 6000 h Rated	94 %		
LSF 16000 h Rated	33 %	LLMF 8000 h Rated	93 %		
LSF 20000 h Rated	2 %	LLMF 12000 h Rated	92 %		
Flux measurement reference	Sphere	LLMF 16000 h Rated	91 %		
		LLMF 20000 h Rated	90 %		
Light technical					
Color Code	840 [ CCT of 4000K]	Operating and electrical	Operating and electrical		
Luminous Flux (Nom)	5240 lm	Power (Nom)	59.4 W		

# **MASTER TL-D Super 80**

Lamp Current (Nom)	0.670 A			
Temperature				
Design Temperature (Nom)	25 °C			
Controls and dimming				
Dimmable	Yes			
Mechanical and housing				
Bulb Shape	T8 [ 26 mm (T8)]			
Approval and application				
Energy Efficiency Class	G			
Mercury (Hg) Content (Nom)	1.7 mg			
Energy Consumption kWh/1000 h	60 kWh			

EPREL Registration Number	423398			
Product data				
Full product code	871150063219740			
Order product name	MASTER TL-D Super 80 58W/840 1SL/25			
EAN/UPC - Product	8711500632197			
Order code	927922084023			
Numerator - Quantity Per Pack	1			
Local code description	2051126986			
Numerator - Packs per outer box	25			
Material Nr. (12NC)	927922084023			
Net Weight (Piece)	167.000 g			
ILCOS Code	FD-58/40/1B-E-G13			

## Dimensional drawing



#### MASTER TL-D Super 80 58W/840 1SL/25

## Photometric data



LDPB\_TL-D8\_840\_0001-Spectral power distribution B/W

Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super	28 mm	1500.0 mm	1507.1 mm	1504.7 mm	1514.2 mm
80 58W/840 1SL/25					





# **MASTER TL-D Super 80**

### Lifetime







LDLM\_TL-D8\_0001-Lumen maintenance diagram



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

LDLE\_TL-D8\_0002-Life expectancy diagram