

Technical specification: Svenco product no. 2100

Paper

Plies:	2 ply sack with extra strong bottom.
Paper weight:	2 x 60 gr/m ²
Quality in/outside ply:	Advantage High Strength Plus WS brown Kraft, Quality 20,18. Width 1470 mm. The paper is certified to be fully compostable in compliance with EN 13432
Quality inner bottom:	Advantage High Strength Plus ½ WS brown Kraft, Quality 03/70 gr/m ² . Width 360 mm. The paper is certified to be fully compostable in compliance with EN 13432
Quality outer bottom:	Advantage High Strength Plus ½ WS brown Kraft, Quality 02/70 gr/m ² . Width 450 mm. The paper is certified to be fully compostable in compliance with EN 13432
Measurement:	75 x 92 x 25 cm / SL-length 105 cm

Glue: Off white Solvicol 1289, a pregelatinized alkali hydrolysed potato starch produced by AVEBE Adhesives, The Netherlands.

Printing: in accordance with customer's instructions

Quality of ink: Water based flexoink, produced by Flint Group. Plain water (H²O) is used as solvent in the ink.

Barcode: in accordance with customer's instructions

Inside printing: in accordance with customer's instructions


Sacks/bundle: 50

Bundles/pallet: 39

Straps: 2 Strapex straps / bundle.

Date: Arlandastad 2023-05-25 valid 2 years from date.

Svenco Papperssäcker AB



Jan Persson

Managing director



Papperssäcker Aktiebolag

Maskingatan 10 195 60 ARLANDASTAD ☎ 08-594 405 60
Fax: 08-591 136 60 mail@svenco.se www.svenco.se orgnr: 556008-9186